

INQUIRY DATASHEET

Example type designations:

M20-L-B7	Segment-screw clamp	M20 = metric thread	L = Clamping length, see dimension sheet 111	B7 = Material
WU-M20-L-B7	WU = Wulst-screw clamp		L = Clamping length, see dimension sheet 111 special	
DIN-M20-60-85-B7	DIN = DIN-screw clamp		60-85 = Clamping length, see dimension sheet 112	

eff. clamping area

Segment-Screw Clamp (Pressure Vessel Clamp)

Wulst-Screw Clamp, similar DIN 28152

DIN 28152-Screw Clamp

Hexagon Nut

Execution: H=D H=1,2xD DIN2510/NF DIN ISO 4033

Other Nuts

Execution: Cap Nut Wing Nut

No. of items: _____

Material according to AD Code :

"A4" = 1.4571 (x6CrNiMoTi17-12-2)

"B7" = 1.7225 (42CrMo4)

"W" = 1.7709 (21CrMoV5-7)

"W" = 1.7218. (25CrMo4) (for DIN 28152-clamp screw only)

Material according to ASME Code :

"B8M" = SA-193 / Gr. B8M

"B7" = SA-193 / Gr. B7

Certificate acc.:

inspection certificate 3.1 acc. EN 10204:2004

inspection certificate 3.2 acc. EN 10204:2004, incl. proof at 500°C

inspection certificate 3.2 acc. EN 10204:2004

inspection certificate 3.2 acc. EN 10204:2004, incl. proof at

other: _____

minus temperature - _____ °C

without

Certification acc.:

AD 2000

ASME

other: _____

without

Surface Treatment:

veralisert

galvanized (blue / yellow): _____

electropolished

pickled & passivated

chemically nickel

other: _____

hard chrome plated

without

Desired Delivery Date: _____